

List of Figures

Figure 1-1: Ball screw (Rexroth Bosch AG, 2006:1)	1
Figure 2-1: KAT-7 main assemblies (BAE Systems Dynamics, 2010:1)	6
Figure 2-2: Paraboloidal reflector (BAE Systems Dynamics, 2010:1)	7
Figure 2-3: Axes systems	8
Figure 2-4: Elevation angle θ (BAE Systems Dynamics, 2010:1)	9
Figure 2-5: Azimuth angle ψ (BAE Systems Dynamics, 2010:1)	9
Figure 2-6: Ball screw nut (Rexroth Bosch Group, 2009:46)	10
Figure 2-7: Ball screw spindle (Rexroth Bosch Group, 2009:64)	11
Figure 2-8: Flow of forces (Rexroth Bosch AG, 2006:9)	11
Figure 2-9: Bi-directional external applied force (ISO 3408-5, 2006:12)	12
Figure 2-10: Tensile test stress-strain curve for mild steel (Shigley, 2003:257)	14
Figure 2-11: Compression test samples (KOÇAK, 2003:91)	15
Figure 2-12: Compression stress-strain curve for steel (Caccialupi, 2003:11)	16
Figure 2-13: Tensile and compression stress-strain comparison (Ellermann and Scholtes, 2014:10)	17
Figure 2-14: Compressive stress-strain curve of 100Cr6 at various temperatures (Hor et al., 2013:7)	17
Figure 2-15: Schema Brinelling and False Brinelling (Massi et al., 2010:1069)	19
Figure 2-16: Comparative results of finite element analysis and Hertzian analysis (Song and Komvopoulos, 2013:94)	20
Plate 3-1: Mounted samples in bakelite for optical microscopy	24
Figure 3-2: Basic view of elevation mechanism (BAE Systems Dynamics, 2010:1)	27
Figure 3-3: Elevation mechanism (BAE Systems Dynamics, 2010:1)	28
Figure 3-4: Paraboloidal reflector free body diagram	29
Figure 3-5: Torque arm representation due to raceway helix angle	32
Figure 3-6: Raceway helix angle representation	33
Figure 3-7: Forces acting on helix angle representation	33
Figure 3-8: Approximated helix angle of the ball screw thread	34
Figure 3-9: Water volume and drainage holes (BAE Systems Dynamics, 2010:1)	39
Figure 3-10: Paraboloidal reflector layout (SKA Africa, 2008:46)	40
Figure 3-11: Oblique parabolic segment	42
Figure 3-12: Segment area	42

Figure 3-13: Multiple parabolic volume segments	44
Figure 3-14: Parabolic segment centroid	44
Figure 3-15: Multiple parabolic volume segments	45
Figure 3-16: Paraboloid front and side views (ESDU, 2006:3)	46
Figure 3-17: Effect of f/d on transverse force coefficient for plain isolated paraboloids (ESDU, 2006:15)	48
Figure 3-18: Effect of f/d on axial force co-efficient for plain isolated paraboloids (ESDU, 2006:14)	49
Figure 3-19: Effect of f/d and a/d on moment about vertex for plain, isolated paraboloids (ESDU, 2006:15)	50
Figure 3-20: Force and moment coefficient components in a vertex axis system	51
Figure 3-21: Structural mass, F_{zc}	53
Figure 3-22: Off-set error representation	56
Figure 3-23: Assembly steps one, two and three	57
Figure 3-24: Assembly step one	58
Figure 3-25: Assembly steps four, five and six	59
Figure 3-26: Installation of the last ball bearing	60
Figure 3-27: Completed assembly	61
Figure 3-28: Compression test in progress	62
Figure 3-29: Raceway and indenter assembly	63
Figure 3-30: Mesh on raceway surface	65
Figure 3-31: Mesh on ball bearing indenter	65
Figure 4-1: Replica KAT-7 ball screw spindle case depth	71
Figure 4-2: Force, F_0 , and, F_a , results of load case scenario one	79
Figure 4-3: Weighted percentage error results of load case scenario one	80
Figure 4-4: Variable length S_7 of load case scenario one	81
Figure 4-5: Force, F_0 , and, F_a , results of load case scenario two	82
Figure 4-6: Weighted percentage error result of load case scenario two	83
Figure 4-7: Load case scenario three's force, F_0 , results	86
Figure 4-8: Weighted percentage error results of load case scenario three	87
Figure 4-9: Force, F_0 , results of load case scenario four	89
Figure 4-10: Weighted percentage error results of load case scenario four	90
Figure 4-11: Force, F_0 , results of load case scenario five	92
Figure 4-12: Compression test data and numerical model data results	93

Figure 4-13: Weighted percentage error for the compression test data and numerical model data	95
Figure 4-14: Raceway Brinelling on a replica KAT-7 ball screw nut	95
Figure 4-15: Compression force, F_a , unique bend indicating yield point	96
Figure 4-16: Brinelled raceway surface under a Hertzian contact stress	97
Figure A-1: Machining drawing of the SPINDLE, BALL SCREW	112
Figure A-2: Machining drawing of the BASE PLATE	113
Figure A-3: Assembly drawing of the base plate and dowel pins	114
Figure B-4: Calibration certificate page 1/2	116
Figure B-5: Calibration certificate page 2/2	117